

# VVT Stealth 64



## Features & Benefits

- 650+ RWHP Peak
- Billet Compressor & Turbine Wheel
- 360 degree Thrust Bearing
- Quick Spool-Up
- Direct Bolt-On
- Great Daily Driving/Towing

Fitment Specifications						
Year	OEM	Models	OEM Part #(s)			
2004.5-2010	Chevy	2500, 3500	736554-5014 736554-0011 736554-5011 736554-9011 736554-0001			
2004.5-2010	GMC	2500, 3500	736554-5001 736554-9001 736554-0002 736554-5002 736554-9002 736554-0003 736554-5003 736554-9007 736554-9008 736554-9014 736554-9003 736554-0004 736554-5004 736554-9004 736554-0005 736554-5005 736554-9005 736554-0006 736554-5006 736554-9006 736554-0007 736554-0008 736554-0014 790032-9003 7900329003 19329915 97387896 98011735 98021617 98065854 12639460 736554- 5015 736554-9015 759622-5005 759622-9005 763333-5005 763333-9005 790032-5004 790032-9004 848212-5001 8482125001 848212-900 8482129001 98011735 19329916 98021617 98065854 8980033661 8980033662 8980117351 98003366 759622-5006 759622-9006 759622-5 759622-0002 759622-5002 759622-9002 759622-5005 759622-0005 759622-9005 R759622-5005 R759622-9005 848212-5001 8482125001			
Measurement Specifications						
Compressor - Wheel Inducer	Compressor - Inducer Bore	Compressor - Wheel Blade Count	Turbine - Wheel Exducer	Turbine - Wheel Inducer	Turbine - Wheel Blade Count	Peak Power
63mm	64mm	6 + 6	67mm	73mm	10	650 RWHP
Maximum Recommended Boost Pressure (psi) for VVT Stealth64						
Altitude (ft)	Barometric Pressure (psi)		Baro (inHG)	Max Safe Boost (psi)		
-1000	15.2		31.02	38		
0	14.7		29.88	36.8		
1000	14.2		28.86	35.5		
2000	13.7		27.84	34.3		
3000	13.2		26.83	33		
4000	12.7		25.81	31.8		
5000	12.2		24.8	30.5		

The VVT Stealth 64 takes a stock appearing LLY/LBZ/LMM turbocharger and overhauls it to meet the demands of the Duramax tuner team. This means your new turbo will spool-up quickly, feel responsive, and most importantly will move for air into your engine! That means more top end power without sacrificing drive-ability.



Home of

